


# Toilet or Closet Flanges

Used to Connect a toilet to the DWV system

## Choose


### Fixed



Minimal adjustment when mounting toilet.

or


### Adjustable



Full 360° adjustment when mounting toilet.


<b>027586</b>	<b>Adjustable</b>	<b>H</b>
<b>027587</b>	<b>Adjustable</b>	<b>Sp</b>
<b>027584</b>	<b>Fixed</b>	<b>H</b>
<b>027585</b>	<b>Fixed</b>	<b>Sp</b>

### Hub (H)



or

### Spigot (Sp)




### Test Plug Flange



- New construction for pressure testing
- Temporary seal until toilet is installed
- Prevents fumes from escaping

<b>027588</b>	<b>Adjustable</b>	<b>H</b>
<b>027591</b>	<b>Fixed</b>	<b>H</b>

## Specialty (Where available)




### Flush Fit

Used in applications where waste pipe is flush with floor surface. Fits **OVER 4"** ABS waste pipe.

**027582**

**Adjustable**

**H**



### Flange Ring

Used as a riser, to build up existing flange when new flooring or ceramic tile has resulted in flange being at or below floor level.

**027002**



### Offset Flange

Used when toilet waste pipe is too close to the wall. Provides 1.5" offset.

**027574**

**Adjustable**

**H**